

SHENZHEN MEICHI ELECTRONICS CO., LTD





2019 PRODUCT

W W W . H O M S C A M . C O M





















H@MSCAM





LOW-POWERED WIFI BATTERY CAMERA

Characteristics:

- # 1080P or 960P, 166° wide viewing angle.
- 36 2.4G WIFI connection. Compatible with IOS. Android, support mobile phone remote wake up the device within 1 second.
- # Support PIR motion detection, alarm push to mobile phone.
- 36 High quality two-way talk with noise cancellation allow you to see, hear and speak to anyone at your door from your phone.
- 26 Day and night mode automatic switching, whether day or night, the image is clearly visible for your safety and family security.
- # Total wireless, plug play 18650 battery for power supply, 4-6 month long stand working time, smart relay station, which max supports 64GB SD card.

Items	Specification	
APP	HOMSCA VIEW	
Main Processor	Hi3518E	
Camera Resolution	1920*1080 pixels or 1280*960 pixels	
mage Sensor	1/3 CMOS	
/ideo	H.265	
System	Lite OS	
D/N mode	IR-CUT double filter automatically switches	
R distance	850nm IR distance 5m	
Audio	Audio code standard, AAC & G.726	
	Audio input/output, -38dB microphone / build-in speaker	
/iewing Angle	166° wide-angle lens	
Day & Night	Color / B&W (IR-CUT)	
Connection	Wi-Fi 2.4 GHz, IEEE 802.11b/g/n	
	AP hot spot	
	Scan QR code	
letwork protocol	TCP/IP, HTTP, TCP, UDP, SMTP, DHCP, DNS, P2P	
Storage	Smart phone local record, video playback	
	Support device record, video playback	
Wake up	Smart phone remote active wake-up	
	PIR wake up	
Motion Detection	PIR motion detection with adjustable sensitivity (2 seconds)	
	/ (5 seconds) / (10 seconds)	
Sharing	Support QR code sharing, share up to 7 users, and support	
	3-4 users while watching online ((Mainly depends on	
	whether the network signal of the user's home is strong	
	and stable.)	
Battery	3.7V, 2pcs 18650 batteries, rechargeable (8V~24V AC AC)	
Working temperature	-10°C ~+50°C	
remaining remaperature		

W W W . H O M S C A M . C O M

















Characteristics:

H@MSCAM

- ₩ WiFi Bicycle Rearview Camera
- # Free iOS & Android APP available in APP store
- # Built-in Li-battery for 5 hours working
- ₩ Wireless transmission distance 10m/50 ft.

Items	Specifications
Image sensor	1/4",CMOS
Pixels	1280x720
Field of viewing angle	110° ±5°
Waterproofing grade	Ip55
Video Resolution	HD: 1280x720P/15fps VGA: 640x480P/20fps
Video compression	H.264
Transmission distance	≥10m
Wireless standard	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Battery capacity	2200mAH
Consumption current	230±20mA
Charging current	450±20mA
Adapter	5V (Micro USB) 6V (Micro USB AC)
Battery working time	4H±20mA
Charging time	5H±10mA
Dimensions (W x D x H)	85*115*56
Operation Temperature	-10°C~+45°C
Operation Humidity	15%~85%RH
Weight	0.12kg

W W W . H O M S C A M . C O M











LOW - POWERED SMART WIF I DOORBELL

- 36 Million HD pixels collocated with 166" wide-angle lens and high quality two-way talk with noise cancellation allow you to see, hear and speak to anyone at your door from your
- # The APP will push notification to your smart phone. 720P 25fps smooth video streaming when someone hovers at the door and trigger ring's built-in motion sensors.
- PIR is triggered.
- * Total wireless, plug play 18650 battery for power supply, 4-6 month long stand working time,
- 36 It can be made into the TUYA version.
- 96 Our HSC192 has the appearance patent, HSC192&HSC194 are waterproofs

Items	Specification
APP	HOMSCA VIEW
Main Processor	Hi3518E
Image Sensor	1/4" CMOS
Video Compression	H.264
Camera Resolution	1280*720 pixels
Audio	Two-way voice with echo cancellation Built-in Speaker Built-in Mic
Viewing Angle	166° wide-angle lens
Day & Night	Color / B&W (IR-CUT) 6pcs infrared LED 850mm Low illumination: 1Lux
Connection	Wi-Fi 2.4 GHz, IEEE 802.11 b\g\n AP hot spot Scan QR code
Record	Smart phone local record, video playback Support device record, video playback
Screenshot	Smart phone real time screenshot
Wake up	Smart phone remote active wake-up PIR wake up Device button wake up
Motion Detection	PIR motion detection with adjustable sensitivity (2 seconds) /(5 seconds) / (10 seconds)
Sharing	Support QR code sharing, share up to 7 users, and support 3-4 users while watching online ((Mainly depends on whether the network signal of the user's home is strong and stable.)
Battery	3.7V, 2pcs 18650 batteries, rechargeable (8V~24V AC AC)
Power consumption	Operating current 170mA, standby current 160 µ A

WWW.HOMSCAM.COM

A unique and professional APP was designed for the HOMSCAM Smart Security Light, supporting for



App
Tuya Smartlife

works with amazon alexa

VIDEO SECURITY CAMERA

36 It has a special pre-capture function, when the device is triggered, the video recording

There is a RJ45 interface for wired connection, so that the image transmission is more stable

This new version has the external SD card port, so reading the information is more

There is an alarm function. After clicking on the APP, the sound of the alarm will be issued

HOMSCA LIGHT 1/2.7" CMOS Inch H.264

1920*1080 pixels

Pan:40° Tilt:40° Manual >15(OFF),<8(ON) Lux

110° ± 5°

AC: 100~240V

DC 5V/1A 450(MAX)mA

-40℃~+55℃(-40°F~+131°F

-40°C~+60°C(-40°F~+140°F 15%~85% RH

home is strong and stable.)

HD:1920*1080/15fps VGA:640*480/2

IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

Dual Streams, Main-2Mbps, Secondary-512kpb Motion Detection+PIR, or APP control

Support QR code sharing, share up to 4 users, and support 4 users while watching online (Mainly depends on whether the network signal of the user's

Human body infrared sensing, avoiding the impact of cats and dogs on device triggering

interception starts 5 seconds before the trigger, which solves the shortcoming that the video

& OUTDOOR LIGHT

Easy installation, support for remote viewing

for 15 seconds to scare off the thief.

₩ Certification: CE FCC ROHS ETL.

Video Compressio Camera Resolution

Video Resolution

Viewing Angle

Alarm Mode

Power Supply

Working Current PIR Detection Distanc

Operation Temperature Storage Temperature

Rotation Angle

Minimum Illuminati

Wireless Standard

only sees the person's back or can't see the face.

Stellar Level Night Vision, the images you see at night are also in color HD.



















- # 2.4G WIFI connection. Compatible with IOS. Android, support mobile phone remote wake
- up the device within 1 second.
- 36 It has PIR sensor, with High sensitivity, perfectly avoid unnecessary alarm, it will record when
- # Day and night mode automatic switching, whether day or night, the image is clearly visible
- smart relay station, which max supports 64GB SD card.

1115	specification	
P	HOMSCA VIEW	
ain Processor	Hi3518E	
age Sensor	1/4" CMOS	
deo Compression	H.264	
mera Resolution	1280*720 pixels	
dio	Two-way voice with echo cancellation	
	Built-in Speaker Built-in Mic	
ewing Angle	166" wide-angle lens	
y & Night	Color / B&W (IR-CUT)	
	6pcs infrared LED 850mm	
	Low illumination: 1Lux	
nnection	Wi-Fi 2.4 GHz, IEEE 802.11 b\g\n	
	AP hot spot	
	Scan QR code	
cord	Smart phone local record, video playback	
	Support device record, video playback	
reenshot	Smart phone real time screenshot	
ake up	Smart phone remote active wake-up	
	PIR wake up	
	Device button wake up	
otion Detection	PIR motion detection with adjustable sensitivity (2 seconds)	
	/ (5 seconds) / (10 seconds)	
aring	Support QR code sharing, share up to 7 users, and support	
	3-4 users while watching online ((Mainly depends on	
	whether the network signal of the user's home is strong	
	and stable.)	
ttery	3.7V, 2pcs 18650 batteries, rechargeable (8V~24V AC AC)	
wer consumption	Operating current 170mA, standby current 160 µ A	

W W W . H O M S C A M . C O M











LOW - POWERED WIFI **BATTERY CAMERA**

Features:

- . Low-power WIFI battery camera
- •1080P, 125° wide-angle lens
- Support PIR motion detection, message push to mobile phone
- •Support Wi-Fi 2.4 GHz, IEEE 802.11b/g/n
- . Support PIR detection and mobile phone active wake-up
- . Two-way intercom, with echo cancellation
- Support cloud storage function
- •Low power consumption 4 * AA5 lithium iron battery

Specification:			
Chip	Hi3516E		
Sensor	1/3 COMS		
	1920*1080@25fps		
Video	H.264		
	Adaptive code stream, adapt to multiple network modes (WIFI 3G 4G)		
	Two-way voice intercom, with echo cancellation		
Audio	built-in 1 speaker		
	built-in 1 microphone		
Lens angle	125degree wide angle		
	IR-CUT dual filter automatic switching		
Day/Night	11pcs IR LED 850mm (5~8M)		
	Low illumination:1 Lux		
	Support Wi-Fi 2.4 GHz, IEEE 802.11 b\g\n		
Connection	AP hot point connect		
Storage	Could storage		
B	Support mobile phone recording, video playback on demand		
Recording	Support device recording, video playback on demand		
Screenshot	Live screenshot by mobile		
Wake up proactively	Waken up by mobile phone and PIR		
Quick start	System start within millisecond		
Push message	Fast push 12s		
Motion detection	PIR motion detection, adjustable sensitivity(2s)/ (5s)/ (10s)		
Other features	BLC		
	Strong light suppression		
	Rapid movement		
users	Support account sharing, up to 7 users, and support 3 users to watch online at the same time		
Power	1.5V, 4* AA5 battery, (non-rechargeable)		
Power consumption	Working electric current: 250mA, standby electric current: 160µA		

W W W . H O M S C A M . C O M









LOW-POWERED WIFL BATTERY CAMERA

Features:

- ·Low-power WIFI battery camera
- •1080P, 125° wide-angle lens
- •Support PIR motion detection, message push to mobile phone
- •Support Wi-Fi 2.4 GHz, IEEE 802.11b/g/n
- . Support PIR detection and mobile phone active wake-up
- •Two-way intercom, with echo cancellation
- Support cloud storage function
- •Low power consumption 4 * AA5 lithium iron battery

Specification:		
Chip	Hi3516E	
Image sensor	1/2.7" 1.3MP CMOS	
Lens/ Visual Angel	4mm@F1. 2 / 104°	
IR compensate	6 infrared light, Max distinguish distance 5M	
Audio	built-in 38dB microphone(Pickup distance 5M); Built-in speaker (8Ω 1W)	
On-board storage	Support external 32 GB Micro TF card	
Connection mode	Wi-Fi(802.11b/g/n@2.4G)	
Transmission distance	Outdoor: 50 meters, indoor:10 meters (depending on the environment)	
Monitoring	Motion Detection/Remote Live View	
Waterproof grade	IP66	
Power&Endurance	18650 Batteries, DC5V-1A, AC8-24V, Batteries work regularly for3-4	
time	months	
Solar power	1W	
working temperature	Resting state 200uA; working condition 250mA@3.7V	
Dimension	180*90*90	
Weight	370g	

W W W . H O M S C A M . C O M





1080P Baby monitor

Items	Specifications
Camera	
Image sensor	1/2.7",CMOS F22
Camera Resolution	1920*1080
Camera Rotation Range	Horizontal(350°), Vertical (90°)
Night Vision Range	5m
Operation Temperature	-10~+50℃
Operation Humidity	15%~85%
Dimension(W*D*H)	91*91*103mm
Weight	300g
Receiver	
LCD	5 INCH
Efective pixel	800*480
Wireless transmission way	Wi-Fi
Power supply	DC 5V/2A
Poeration Temperature	0~+50°C
Storage Temperature	-20°C~+60°C
Operation Humidity	0~75%RH
Dimension(W*D*H)	165*98*30MM
Weight	370g

W W W . H O M S C A M . C O M







LOW-POWERED SMART WIF I DOORBELL



W W W . H O M S C A M . C O M





SHENZHEN MEICHI ELECTRONICS CO., LTD., founded in 2006 in Shenzhen.

is a leading professional high-tech company which provides IP video camera and solutions in China.-Meichi is committed to offering the public the safest network

camera series of high quality and cost-effective comprehensive equipment solutions.

611 Room, C-Building, Xinyidai Information Tech Industry Park, ChuangYe 2nd Road, Bao'an district, Shenzhen City

mail: sales@homscam.com

W W W . H O M S C A M . C O M